



Service Drop Quadruplex, AAAC Messenger, 1350 Aluminum Conductors, 90 °C Dry or Wet, Rated 600 V



APPLICATIONS

Used for secondary distribution and overhead service entrance at 600 V or less, rated 90 °C dry or wet, sunlight resistant.

CONSTRUCTION

Phase Conductor: Compact stranded All Aluminum Conductor (AAC) 1350.

Insulation: Sunlight resistant Cross-Linked Polyethylene (XLPE).

Neutral or Messenger: Concentric stranded bare All Aluminum Alloy Conductor (AAAC) 6201-T81.

Assembly: Twisted assembly of 3 insulated phase conductors around 1 bare neutral or messenger conductor.

CONDUCTOR IDENTIFICATION

Phase A: Black and marked "PHASE A"

Phase B: Black and marked "PHASE B"

Phase C: Black and marked "PHASE C"

VOLTAGE RATING: 600 V

RATINGS AND MARKINGS

Sunlight resistant and marked
RoHS Compliant

STANDARDS

These cables are manufactured and tested to meet or exceed the following standards:

- ASTM B230 – Aluminum 1350-H19 Wire for Electrical Purposes
- ASTM B231 – Concentric-Lay-Stranded Aluminum 1350 Conductors
- ASTM B398 – Aluminum-Alloy 6201-T81 and 6201-T83 Wire for Electrical Purposes
- ASTM B399 – Concentric-Lay-Stranded Aluminum-Alloy 6201-T81 Conductors
- ASTM B400 – Compact Round Concentric-Lay-Stranded Aluminum 1350 Conductors
- ICEA S-76-474 – Neutral Supported Power Cable Assemblies with Weather Resistant Extruded Insulation Rated 600 Volts

TEMPERATURE RATING

Dry or Wet 90°C

MINIMUM BENDING RADIUS

Not Under Tension: 19x outer diameter
Under Tension (During Pull): 29x out diameter

Code Word	Phase Conductor				6201 Neutral Conductor			Overall Diameter (in)	Weight		
	Size (AWG or kcmil)	Stranding	Insulation Thickness (in)	Diameter (in)	ACSR Equivalent Size (AWG or kcmil)	Actual Size (kcmil)	Stranding		Phase Al (lb/1000 ft)	Neutral Al (lb/1000 ft)	Net (lb/1000 ft)
Bay	6	Solid	0.045	0.252	6	30 580	7	0.608	74.1	28.5	144
French-Coach	6	7	0.045	0.259	6	30 580	7	0.625	75.3	28.5	146
German-Coach	4	Solid	0.045	0.294	4	48 690	7	0.710	117.5	45.4	212
Arabian	4	7	0.045	0.303	4	48 690	7	0.732	119.6	45.4	216
Belgian	2	7	0.045	0.358	2	77 470	7	0.864	190.3	72.2	325
Shetland	1/0	19	0.060	0.456	1/0	123 000	7	1.101	302.6	114.9	523
Thoroughbred	2/0	19	0.045	0.496	2/0	155 400	7	1.197	381.9	144.9	643
Trotter	3/0	19	0.045	0.543	3/0	195 700	7	1.311	481.0	182.5	792
Walking	4/0	19	0.045	0.595	4/0	246 900	7	1.436	607.1	230.2	979